SMS

SHIELD MINI SIGHT

THE ORIGINAL MINI PISTOL RED DOT SMS





SMS- TECHNICAL SPECIFICATION

Optical characteristics	
Light Source	Red light emitting diode (LED) No laser; completely eye safe No radioactive materials
Red Dot Size Options	2MOA, 2 MOA + 65 MOA ring, 4 MOA dot, 8 MOA dot (NSN 1240-99-555-2800)
Lens	Crystal Clear 1x Hard Dip Coated Acrylic Lens, Parallax-free.
Lens Coating	Anti-reflection No coloured coating, minimises visible signature
Electronics	
Battery	One 3V lithium battery, CR2032
Battery Life	20,000H at average daylight with a 2032 at 70°f (21°C)
Brightness Adjustment	Automatic
Brightness Range	Lowest – compatible with Night Vision Highest – visible against the sky in bright daylight
Exterior	
Housing material	Glass-filled polymer Optional rain cover
Colour	Matte black
Dimensions Sight only	(Length x width x height) 42 x 25 x 23 mm 1.7 x 1.0 x 0.9 inches
Weight	14 grams / 0.5 ounces
Mount	The SHIELD Footprint - 100+ Mounting solutions.

THE ORIGINAL

The first micro open red dot released to the market in 1996, originally branded Firepoint and later, the Optima 2000 by Tasco. Our starting point in the industry and benchmark against all our products. Still in service and available in the market for nearly 30 years, the SMS has truly set the standard in the micro red dot world and continues to be a choice for many.

SMS







RETICLE OPTIONS

